



# Wall mounted unit

FTXC-D + RXC-D

**BLUEEVOLUTION** sensira



Onecta app (optional)




Energy saving during standby mode

Wall mounted unit, offering good value for money

- › Flat, stylish front panel blends easily with any interior décor and is easier to clean
- › Onecta app (optional)
- › Seasonal efficiency values up to A++ in cooling
- › Blueevolution range: lower environmental impact

# FTXC-D + RXC-D



Indoor unit				FTXC	20D	25D	35D	50D	60D	71D	
Dimensions	Unit	HeightxWidthxDepth	mm	288 x770 x234					297 x990 x273		
Weight	Unit		kg	9.00			9.50		13.0		
Air filter	Type			Removable / washable							
Fan	Air flow rate	Cooling	Silent operation/ Low/Medium/ High	m <sup>3</sup> /min	5.4 /6.1 /8.1 /10.8		5.4 /6.4 /8.7 /11.1	7.4 /8.1 /9.9 /12.5		10.2 /12.5 /14.5 /20.4	
Sound power level	Cooling			dB(A)	57			58	60		63
Sound pressure level	Cooling	Silent operation/Low/High		dB(A)	21 /26 /40		22 /26 /41	30 /33 /47		31 /38 /48	
Control systems	Infrared remote control				ARC486A2						
	Wired remote control				-						

Outdoor unit				RXC	20D	25D	35D	50D	60D	71D	
Dimensions	Unit	HeightxWidthxDepth	mm	550 x658 x273					615 x845 x300		695 x930 x350
Weight	Unit		kg	24.0			26.0	39.0		45.0	
Sound power level	Cooling			dB(A)	58			60	65	66	69
Sound pressure level	Cooling	High		dB(A)	45			46	51	54	
Operation range	Cooling	Ambient	Min.~Max.	°CDB	10 ~46					-10 ~46	
	Heating	Ambient	Min.~Max.	°CWB						-15 ~18	
Refrigerant	Type				R-32						
	GWP				675.0						
	Charge			kg/ TCO2Eq	0.550 /0.371		0.750 /0.506	1.00 /0.675	1.10 /0.743	1.15 /0.776	
Piping connections	Liquid	OD		mm	6.35						
	Gas	OD		mm	9.52			12.7		12.7	
	Piping length	OU - IU	Max.	m	20			30		30	
	System	Chargeless		m	8						
	Additional refrigerant charge			kg/m	0,017 (for piping length exceeding 7.5m)						
	Level difference	IU - OU	Max.	m	15.0			20.0		20.0	
Power supply	Phase/Frequency/Voltage			Hz/V	1~/50 /220-240						
Current - 50Hz	Maximum fuse amps (MFA)			A	16						

Efficiency data				FTXC + RXC	20D + 20D	25D + 25D	35D + 35D	50D + 50D	60D + 60D	71D + 71D
Cooling capacity	Min./Max.		kW	1.3 /3.0		1.3 /4.0		1.4 /6.2	1.8 /7.0	2.3 /7.3
Heating capacity	Min./Max.		kW	1.30 /4.00						
Power input	Cooling	Min./Nom./Max.	kW	0.30 /0.595 /1.15	0.30 /0.765 /1.15	0.32 /1.05 /1.74	0.30 /1.55 /2.11	0.38 /1.89 /2.05	0.44 /2.38 /2.54	0.44 /2.38 /2.54
	Heating	Min./Nom./Max.	kW	0.28 /0.670 /1.35	0.28 /0.750 /1.35	0.28 /1.07 /1.57	0.27 /1.52 /1.85	0.33 /1.68 /2.35	0.50 /2.46 /2.74	0.50 /2.46 /2.74
Space cooling	Energy efficiency class			A++						
	Capacity	Pdesign	kW	2.08	2.57	3.44	5.08	6.21	6.96	6.96
	SEER			6.89	6.84	6.87	6.45	6.40	5.30	5.30
	Annual energy consumption		kWh/a	106	131	175	276	339	460	460
Space heating	Energy efficiency class			A+						
(Average climate)	Capacity	Pdesign	kW	1.87	2.23	2.24	3.90	4.10	6.35	6.35
	SCOP/A			4.40	4.45	4.28	4.42	4.24	3.81	3.81
	Annual energy consumption		kWh/a	595	701	733	1,234	1,353	2,332	2,332
Nominal efficiency	EER			3.36	3.35		3.29	3.30	2.98	2.98
	COP			3.73	3.79	3.74	3.71	3.81	3.25	3.25
	Energy labeling	Cooling/Heating		A/A						
	Directive			C/C						
Current - 50Hz	Maximum fuse amps (MFA)		A	16						

Daikin Europe Naamloze Vennootschap · Zandvoordestraat 300 · 8400 Oostende · Belgium · <https://www.daikin.eu/> · BE 0412 120 336 · RPR Oostende (Responsible Editor)

**Roosmijn Techniek B.V**  
 Steurstraat 51  
 1317 NZ Almere  
 036- 7857069  
 (Open op afspraak)



Daikin Europe N.V. participates in the ECP programmes for Fan Coil Units and Variable Refrigerant Flow systems. Daikin Applied Europe S.p.A. participates in the ECP programmes for Liquid Chilling Packages and Hydronic Heat Pumps. Check ongoing validity of certificate: [www.eurovent-certification.com](http://www.eurovent-certification.com)

ECPEN23-045

01/2023



The present leaflet is drawn up by way of information only and does not constitute an offer binding upon Daikin Europe N.V. Daikin Europe N.V. has compiled the content of this leaflet to the best of its knowledge. No express or implied warranty is given for the completeness, accuracy, reliability or fitness for particular purpose of its content and the products and services presented therein. Specifications are subject to change without prior notice. Daikin Europe N.V. explicitly rejects any liability for any direct or indirect damage, in the broadest sense, arising from or related to the use and/or interpretation of this leaflet. All content is copyrighted by Daikin Europe N.V.